

Model: MARVEL PUL. 59,6X120(A) Codes: 100316046 Water absorption: BIa - Porcelanico (E<=0.1%)







DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Thickness	11.3 MM	+/-5%*		
Width	596 MM			
Length	1200 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		
*ISO-13006:2018 UNE-EN 14411:2016				

MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11				
Breaking strength	3491 N	>1300N*		
Modulus of rupture	52,4 N/MM2	>=35N/mm2*		
Abrasion resistance	PEI 5 / 12000v			
Crazing resistance	Resists 3 cycles			
*ISO-13006:2018 UNF-EN 14411:2016				

HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995				
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*		
Stain resistance	Class 5. Easy cleaning with water	3 Min.*		
Stain resistance *ISO-13006:2018 UNE-EN 14411:2016	X P	3 Min.*		

SCOPE OF USE

Technical code-1

Use on medium traffic floors

ANTI-SLIP VALUE UNE 41901:2017 EX, UNE 41902:2017 EX, DIN-51130 y ASTM C1028

Slip resistance (pendulum-wet)

*ISO-13006:2018 UNE-EN 14411:2016

	PACKING	
Sales units per box	1.4304 M2/BOX	
Sales units per pallet	40.0515 M2/PAL	
Sales units per unit	0.7152 M2/PIECE	





Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

CLO