Model: ADVANCE 1L NUDE Codes: 100317044 Group: G-244 Format: 218X19,8X1,4CM

ADDITIONAL NOTES

Due to better usage of the wood, any order of this reference may contain mean percentage boards of between 15% y 20%. While the color of the skirting boards, profiles, and step borders may vary depending on the model, the color shall be as similar as possible to the wood floor.

COMPOSITION							
		Size	Material	Type of material			
	Layer 1	0.060-0.070	Varnish	Apresto Mate treatment			
	Layer 2	3	Hardwood Layer	Oak wood			
	Layer 3	9	Intermediate Layer	Wood or HDF slats			
	Layer 4	2	Backside	Coniferous wood			

LABORATORY TESTS							
Resistance to abrasion	≥500	UNE-EN 13696*					
Thermal conductivity	0.17 W/M*K	UNE-EN 12667:2002*					
Heat resistance	0.082 M2*K/W	UNE-EN 12667:2002*					
Formaldehyde emissions	E1	EN 717*					
Gluing resistance	≥D3	EN 204*					
Moisture content	5-9 %	UNE-EN 13183-1/AC:2004*					
Flammability	Dfl-s1	EN 13501*					
Bulk density	785 KG/M3	UNE-EN 323:1994*					
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*					
Slip resistance (pendulum-wet)	CL 1 (30)	UNE 41901*					
Slip resistance (pendulum-dry)	CL 3 (50)	UNE 41902*					
Slip resistance (dcof)	0.43	ANSI A137.1*					



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

100317044 ADVANCE 1L NUDE

L'ANTIC COLONIAL

FEATURES							
Ð	Safety and joint durability are the main features of that guarantees the elimination of gaps between bo lifetime. The pressure exerted between boards rein prevents it from being carried out incorrectly.	ards throughout the floor's	۲	Slight smoothing of the wood using a brush to achieve a surface with a slight relief.			
	Applying a color oil or varnish on the wood surface i ranges.	in order to get different color	\oplus	Beveled cut on all 4 edges of the board for emphasizing size			
AM	L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the porces are sealed, dirt and dust remain on the surface and can be easily cleaned.		30	Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.			
	Is suitable for installing on water radiant heating		\bigcirc	Format where only one board has been used to finish the entire base surface			
•	Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.		Ś	It is necessary to apply adhesive for installing it.			
0	Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.		ОАК	Made with oak wood.			
	There are consistent color changes between pieces.		\bigcirc	Material from a North American country.			
	Material from a European country.			PanEuropean Forest Certification that guarantees to consumers the origin of products from sustainably managed forests			
۲	Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.			3 mm			
Ś	It is necessary to apply adhesive for installing it.		0	Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.			
		PAC	KING				
Sales u	inits per box	3.02148 M2/BOX					
Color I	units nor pollot	105 751700 M2/DAL					

Sales units per pallet	105.751799 M2/PAL	
Sales units per square meter	1 M2	
Sale unit	M2	
Base unit	ST	
Net weight	12.023909 KG/M2	
Gross weight	12.482625 KG/M2	

SPECIAL PIECES											
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight		
100317026	IGUALACION ADVANCE NUDE 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES		
100317027	MAMPERLAN ADVANCE 1L NUDE 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES		
100317029	TRANSICION ADVANCE NUDE 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES		
100317052	ZOCALO ADVANCE NUDE 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES		



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.