## L'ANTIC COLONIAL

Model: AUTHENTIC 1L BRONZE

Codes: 100171976 Group: G-265

Format: 24X220X1,35CM



## **ADDITIONAL NOTES**

Due to better usage of the wood, any order of this reference may contain mean percentage boards of between 20% y 25%.

COMPOSITION							
		Size	Material	Type of material			
	Layer 1	0.060-0.070	Oil	Natur Plus treatment			
	Layer 2	3.5	Hardwood Layer	Oak wood			
	Layer 3	10	Intermediate Layer	Softwood veneer			

LABORATORY TESTS							
Mass per surface	7.41 KG/M2	EN 14342*					
Thermal conductivity	0.133 W/M*K	UNE-EN 12667:2002*					
Heat resistance	0.09 M2*K/W	UNE-EN 12667:2002*					
Formaldehyde emissions	E1	EN 717*					
Gluing resistance	≥D3	DIN EN 204*					
Resistance to chair castors	No damage	DIN EN 425*					
Moisture content	7.00%	UNE-EN 13183-1/AC:2004*					
Flammability	Dfl-s1	EN 13501*					
Slip resistance (pendulum-wet)	CL 2 (40)	UNE 41901*					
Slip resistance (pendulum-dry)	CL 3 (50)	UNE 41902*					
Slip resistance (dcof)	0.55	ANSI A137.1*					





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

18/08/2023

## L'ANTIC COLONIAL

## **FEATURES**



It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly



Applying a color oil or varnish on the wood surface in order to get different color ranges



Slight smoothing of the wood using a brush to achieve a surface with a slight relief.  $% \label{eq:controlled}$ 



Beveled cut on all 4 edges of the board for emphasizing size



Combination of oils and natural waxes with air drying that leave the wood with open pores. This type of oil penetrates into the wood continuously, even when it is fitted, so that it may have a 'dry' look when opened to be installed. Advantages: Easy repair of dents and scratches, very natural look, and easy maintenance with the right products. Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



Is suitable for installing on water radiant heating



Format where only one board has been used to finish the entire base surface



Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



It is necessary to apply adhesive for installing it.

There are consistent color changes between pieces.



Material from a North American country.

Made with oak wood.



Material from a European country.



PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests



Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.



3.5 mm



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



It is necessary to apply adhesive for installing it.

	PACKING
Sales units per box	3.168 M2/BOX
Sales units per pallet	104.544 M2/PAL
Sales units per square meter	1 M2
Sale unit	M2
Base unit	ST
Net weight	7.632576 KG/M2
Gross weight	8.096591 KG/M2

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100229309	IGUALACION AUTHENTIC BRONZE 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100176741	MAMPERLAN AUTHENTIC 1L BRONZE 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100229339	TRANSICION AUTHENTIC BRONZE 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100177650	ZOCALO AUTHENTIC BRONZE 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	2.58 KG/PIECES	2.6 KG/PIECES





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

18/08/2023