L'ANTIC COLONIAL

Model: CLASSIC 1L HERRINGBONE BROWN

Codes: 100286519 Group: G-244

Format: 13X72,5X1,4CM



COMPOSITION							
		Size	Material	Type of material			
	Layer 1	0.060-0.070	Varnish	APRESTO MATTE			
	Layer 2	2.5	Hardwood Layer	Oak wood			
	Layer 3	9.5	Intermediate Layer	PINE			
	Layer 4	2.0	Backside	PINE			

TOLERANCES					
Squareness of the item	0.2% of width.				
Curvature	0.1% of length.				

LABORATORY TESTS							
Thermal conductivity	0.14 W/M*K	UNE-EN 12667:2002*					
Heat resistance	0.103 M2*K/W	UNE-EN 12667:2002*					
Formaldehyde emissions	0.024 mg/m3	EN - 717/1:2006*					
Moisture content	7% +/-2%	UNE-EN 13183-1 / AC:2004*					
Flammability	Dfl-S1	UNE EN 13501-1:2007*					
Bulk density	min 500kg/m3	UNE-EN 323:1994*					
Slip resistance (pendulum-wet)	CL 2 (40)	UNE 41901*					
Slip resistance (pendulum-dry)	CL 3 (65)	UNE 41902*					
Slip resistance (dcof)	0.63	ANSI A137.1*					





L'ANTIC COLONIAL

FEATURES



It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly



Slight smoothing of the wood using a brush to achieve a surface with a slight relief.



Applying a color oil or varnish on the wood surface in order to get different color ranges



Beveled cut on all 4 edges of the board for emphasizing size



L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



be easily cleaned.



Format where only one board has been used to finish the entire base surface



Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



It is necessary to apply adhesive for installing it.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



Made with oak wood.



There are consistent color changes between pieces.

Is suitable for installing on water radiant heating



Material from a European country.



Independent (non-governmental) certificate that guarantees consumers that forest products come from rationally exploited forests



Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.



2.5 mm



It is necessary to apply adhesive for installing it.

	Ì

Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.

	PACKING	
Sales units per box	0.65975 M2/BOX	
Sales units per pallet	42.224 M2/PAL	
Sales units per square meter	1 M2	
Sale unit	M2	
Base unit	ST	
Net weight	9.018568 KG/M2	
Gross weight	9.538462 KG/M2	

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100298222	IGUALACION CLASSIC HERRINGBONE BROWN	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100298223	TRANSICION CLASSIC HERRINGBONE BROWN	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100298226	ZOCALO CLASSIC HERRINGBONE BROWN 8X220	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

18/08/2023 2/2