

Model: HARLEM ACERO C-2(R10) L 59,6X59,6(A)

Codes: 100348379

Water absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES  UNE-EN ISO 10545-2			
Thickness	8.5 MM	+/-5%*	
Length and width deviation	Below 0.15%	+/-0.3%*	
Side straightness deviation	Below 0.15%	+/-0.3%*	
Squareness deviation	Below 0.15%	+/-0.3%*	
Surface flatness deviation	Below 0.15%	+/-0.4%*	

<sup>\*</sup>ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES
UNE-EN ISO 10545-4-6-7-11

Crazing resistance Resists 3 cycles

\*ISO-13006:2018 UNE-EN 14411:2016

\*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995		
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

	ANTI-SLIP VALUE EN 16165: 2022 / ASTM C1028
Dynamic coefficient of friction	>0,42
*ISO-13006:2018 UNE-EN 14411:2016	

PACKING		
Sales units per box	1.776073 M2/BOX	
Sales units per pallet	56.834328 M2/PAL	
Sales units per unit	0.355215 M2/PIECE	

SCOPE OF USE		
Technical code-1	6 - Use on heavy traffic floors	

System Certification









## RECOMMENDED USE LOCATIONS

## Single-family dwelling

Indoor Premises - Dry: Room, room, bedroom or other enclosure without direct access to the outdoors.

## Collective housing

Indoor Premises - Residential - Dry: Entrance, living room, dining room, professional office with reception of customers

Indoor Premises - Housing - Dry: Bedrooms, personal office, storage room, changing room

## Various

Cladding of bonded or mixed facades

Facade cladding with mechanical anchors

Kitchen worktops, bars, restaurants

Public bathroom countertops

System Certification





