

Model: LIEM DARK POL. 120X270(6)(A)

Codes: 100332632

Absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES  UNE-EN ISO 10545-2		
Length	2700 MM	
Thickness	6 MM	
Width	1200 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

<sup>\*</sup>ISO-13006:2015 UNE-EN 14411:2017

	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11	
Breaking strenght	>1100 N	
Modulus of rupture	>40 N/MM2	
Abrasion resistance	<140	

<sup>\*</sup>ISO-13006:2015 UNE-EN 14411:2017

	HYGIENIC FEATURES UNE-EN ISO 10545-13-14	
Chemical resistance	MIN B	
Stain resistance	5	_*
Flammability	A1	

<sup>\*</sup>ISO-13006:2015 UNE-EN 14411:2017

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1
Dynamic coefficient of friction	<0.42
Slip resistance (pendulum-wet)	CLO
Pendulum test value (ptv)	DRY>36-LOW_WET<25-HIGH
Slip resistance (pendulum-dry)	>40
*ISO-13006:2015 UNF-FN 14411:2017	

*ISO-13006:2015	UNE-EN	14411:2017

PACKING		
Sales units per box	3.240441 M2/BOX	
Sales units per pallet	71.289695 M2/PAL	
Sales units per unit	3.240441 M2/PIECE	

System Certification







LIEM DARK POLISHED



## ADDITIONAL NOTES

Avoid direct access from the outside if no abrasive protection device is provided.

## **SCOPE OF USE**

Technical code-1 1 - Coating

Technical code-2 0 - No additional requirements

System Certification





