


Model: LINKFLOOR MULTIFORMAT BRONZE


Codes: 100245926

Group: G-230

Format: 8,3/14,6/22,86X152,4X0,55CM



COMPOSITION



	Size	Material	Type of material
Layer 1	0.5	Wear layer	Use layer with PU protection
Layer 2	0.1	Vinyl	decorative film
Layer 3	0.7	Elastic PVC	Intermediate comfort layer
Layer 4	3.2	SPC	SPC composite body
Layer 5	1	IXPE	IXPE motherboard

CERTIFICATIONS

Floorscore certification

FLOORSCORE

ADDITIONAL NOTES

COMPOSITION: Engineered SPC Enhanced Resilient Multi-Layer Vinyl Plank / Tile

FEATURES



Imitates the surface of wood



Water and moisture resistant flooring, suitable for wet areas such as bathrooms and kitchens for residential use, provided the product's installation instructions are followed.



10 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.



Is suitable for installing on water radiant heating



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.



Three different plank widths that allow to create combinations and to obtain unique effects, together with a greater amplitude in the rooms.



Floor capable of dissipating excess electrical charges and distribute them over its entire surface



There are consistent color changes between pieces.

DIMENSIONAL FEATURES

Squareness of the item (q)	0.07 %	ASTM F2199*
Straightness of face	0.13 %	ASTM F2199*



LABORATORY TESTS

Commercial area class	33	EN 10582*
Slip resistance (r)	R-10	DIN 51130*
Abrasion resistance	CLASE T	
Impact resistance	PASS	EN 433*
Castor chair effect	No damage	
Formaldehyde emissions	E1	EN 717-2*
Slip resistance (pendulum-wet)	CL 2 (41)	UNE 41901*
Fire resistance	Bfl-S1	EN 13501*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Heat resistance	0.052 M2*K/W	EN 12667*
Thermal conductivity	0.108 W/M*K	EN 12667*
Uv light fastness	>Grado 6	ISO 105-B02*
Residual footprint	0.06 mm/1%	EN ISO 24343-1*
Acoustic insulation	(6"): IIC=54 dB;STC=51 dB/(7"): IIC=59 dB;STC=54 dB/(8"): IIC=57 dB;STC=52dB/(OWT): IIC=57 dB;STC=61 dB	ASTM E492 ; ASTM E90**
Flexibility	PASS %	EN 435*
Dynamic coefficient of friction	0.55	ANSI 137.1*
Residual footprint	0.00 mm/0%	ASTM F970-15*
Residual footprint	0.03 mm/0.6%	ASTM F1914-07*
Residual footprint	0.22 mm/4%	ASTM F970-17 extended 1000 PSI [≤0.5 mm / ≤9%]*
Resistance to chemicals	PASS	ASTM F925*
Private area class	23	EN 10582*
Slip resistance (pendulum-dry)	CL 3 (80)	UNE 41902*

PACKING

Sales units per box	2.084832 M2/BOX	
Sales units per pallet	116.7506 M2/PAL	
Sales units per unit	2.084832 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Sales units per square meter	1 M2	
Net weight	10.134629 KG/M2	
Gross weight	10.55001 KG/M2	

SPECIAL PIECES

SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100174756	ESP. PERF ADH LINKFLOOR ALUMINIO 3,5X270	G-121	10 PIECES/BOX	1000 PIECES/PAL	10.58 PIECES/M2	-	-	0.37 KG/PIECES	0.39 KG/PIECES
100128267	ZOCALO ALUMINIO 8X225	G-121	12 PIECES/BOX	696 PIECES/PAL	5.56 PIECES/M2	-	-	1.57 KG/PIECES	1.62 KG/PIECES

