







DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Length	1200 MM			
Thickness	6 MM			
Width	1200 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		
*ISO-13006:2015 UNF-EN 14411:2017				

	MECHANICAL FEAT UNE-EN ISO 10545-4-6-	
Breaking strenght	>1100 N	
Modulus of rupture	>45 N/MM2	
Abrasion resistance	<140	
*ISO-13006:2015 UNE-EN 14411:2017		

	HYGIENIC FEATURES UNE-EN ISO 10545-13-14	
Chemical resistance	CLASE A	
Stain resistance	5	
Resistance to thermal shock	RESISTE	
Flammability	A1	
*ISO-13006:2015 UNE-EN 14411:2017		

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1	
Slip resistance (pendulum-wet)	CLO	
4s	DRY>36-LOW_WET<25-HIGH	
Slip resistance (pendulum-dry)	>45	
*ISO-13006:2015 UNE-EN 14411:2017		

SCOPE OF USE

Technical code-1 Technical code-2

Use on light traffic floors Dry interior floors



100288019 VIOLA ROSSE SILK



	PACKING	
Sales units per box	2.88 M2/BOX	
Sales units per pallet	74.88 M2/PAL	
Sales units per unit	1.44 M2/PIECE	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.