

Model: IMAGE SILVER 59,6X150(A)

Codes: 100293271

Water absorption: BIII - Revestimiento (10%<=E<=20%)









| DIMENSIONAL FEATURES UNE-EN ISO 10545-2 | | | | | |
|--|-------------|----------|--|--|--|
| Thickness | 10.5 MM | +/-5%* | | | |
| Width | 596 MM | | | | |
| Length | 1500 MM | | | | |
| Length and width deviation | Below 0.15% | +/-0.3%* | | | |
| Side straightness deviation | Below 0.15% | +/-0.3%* | | | |
| Squareness deviation | Below 0.15% | +/-0.3%* | | | |
| Surface flatness deviation | Below 0.15% | +/-0.4%* | | | |

^{*}ISO-13006:2018 UNE-EN 14411:2016

| MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11 | | | | |
|--|------------------|------------|--|--|
| Breaking strength | 1250 N | >600N* | | |
| Modulus of rupture | 24.2 N/MM2 | >=12N/mm2* | | |
| Crazing resistance | Resists 3 cycles | | | |
| *ISO-13006:2018 LINE-EN 14411:2016 | | | | |

| HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995 | | | | |
|--|--|---------|--|--|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* | | |
| Stain resistance *ISO-13006:2018 LINE-EN 14411:2016 | Class 5. Easy cleaning with water | 3 Min.* | | |

| | SCOPE OF USE | | | |
|------------------------|----------------|--|--|--|
| Technical code-1 | Use on walls | | | |
| PACKING | | | | |
| Sales units per box | 2.6819 M2/BOX | | | |
| Sales units per pallet | 53.6385 M2/PAL | | | |
| Sales units per unit | 0.894 M2/PIECE | | | |

System Certification





